



> PRINT

ECOSYS P5026cdn
ECOSYS P5026cdw
COLOUR PRINTER
FOR A4 FORMAT



THE PRODUCTIVITY BOOSTER.



Speed up your office with this new colour printing device. The high-performance print controller, with its 800 MHz CPU, achieves brilliant colour printout results in no time. Moreover, it comes up with a short warm-up phase and reduces the time-till-first-page printing to 9.5/10.5 seconds for b/w and colour. For even more productivity, the device provides Wi-Fi and LAN and offers mobile printing support for professional and easy output of your documents – ideal for optimised and rapid office tasks.

- > Up to 26 pages per minute in A4 in colour and b/w
- > 1,200 dpi printing quality
- > Standard duplex unit for double-sided printing
- > Fast time to first page: 9.5/10.5 seconds in b/w and colour
- > High performance print controller with 800 MHz CPU
- > Wi-Fi and Wi-Fi Direct as standard*
- > Mobile printing support including AirPrint, Mopria, KYOCERA Mobile Print
- > Compact design with low-noise printing
- > Exceptionally low printing costs in its class

*Only ECOSYS P5026cdw



ECOSYS stands for ECOlogy, ECONomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that toner is the only consumable. The modular design concept allows you to add workflow enhancing functions as required. Integrated system software provides long-term cross network compatibility. KYOCERA's long-life components cost you and the environment less.

Environmental print features

Duplex print mode (Double sided printing), N-Up printing mode (N pages on 1 sheet), Toner save mode (Draft print mode), Quiet mode (reduced print speed).

KYOCERA NetViewer

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

ECOSYS P5026cdn/ECOSYS P5026cdw

GENERAL

Technology: KYOCERA ECOSYS, Colour Laser

Control panel: 2 line LCD back lit display

Engine speed: Up to 26 pages A4 per minute in colour and b/w

Resolution: 1,200 x 1,200 dpi print at reduced speed, multibit technology for print quality of up to 9,600 x 600 dpi (print), 600 x 600 dpi

Duty cycle: Max. 50,000 pages per month

Warm-up time: Approx. 29 seconds or less

Time to first print: Approx. 9.5/10.5 seconds or less in b/w/colour

CPU: 800MHz

Memory: Standard 512 MB, max. 512 MB

Standard interface:

ECOSYS P5026cdn: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Slot for optional SD/SDHC-Card

ECOSYS P5026cdw: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Wireless LAN, Slot for optional SD/SDHC-Card

Dimensions (W x D x H): Main unit: 410 x 410 x 329 mm

Weight: Main unit: Approx. 21 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption:

Printing: 375 W

Ready mode: 33 W

Sleep mode: 0,9 W

Noise (Sound pressure level: ISO 7779/ISO 9296):

Printing in colour: 49/49 dB(A) LpA

Ready/Standby mode: 30 dB(A) LpA

Sleep mode: Immeasurably low

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 50-sheet multi-purpose tray; 60–220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm–216 x 356 mm) 250-sheet universal cassette; 60–163 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148–216 x 356 mm). Max. input capacity with options: 550 sheets

Duplex functionality as standard: Double-sided printing: 60–120 g/m²; A4, A5, B5, Letter, Legal

Output capacity: Max. 150 sheet face down

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc

Emulations: PCL 6 (PCL 5c/PCL-XL), PostScript 3 (KPDL 3), PDF Direct Print, XPS Direct Print

Operating systems: All current Windows operating systems, MAC OS X Version 10.8 or higher, Unix, Linux as well as other operating systems on request

Fonts/Barcodes: 93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19798

Toner-Kit TK-5240K: black toner yield 4,000 pages A4

Starter toner: black toner yield 1,200 pages A4

Toner-Kit TK-5240C, TK-5240M, TK-5240Y: cyan,

magenta, yellow toner yield 3,000 pages A4

Starter toner: cyan, magenta, yellow toner yield 1,200 pages A4

Command Center RX

The Command Center RX enables to control and manage various settings by accessing the device via Web browser.

USB Host Interface for USB Flash Memory

Documents can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

Application-based Profiles

The KX printer driver can create a direct link between dedicated applications and predefined or customised print profiles. You can set that all documents from a user or an application be printed in b/w with activated duplex mode as standard, thus leading to a reduced toner and paper consumption.

OPTIONS

PF-5110 Paper feeder: 250 sheets; 60–163 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148 mm–216 x 356 mm)

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B):

Support for various authentication keys available


CB-510: Wooden cabinet

WARRANTY

2-years warranty** as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 100,000 pages A4 (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.



OCT2016/ECOSYS/P5026CDN/P5026CDW



KYOCERA Document Solutions Belgium N.V.
Sint-Martinusweg 199-201 – 1930 Zaventem – Belgium
Tel +32 (0)2 720 92 70 www.kyoceradocumentsolutions.be

KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri
Chuo-Ku – Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Depending on the country

YOUR KYOCERA BUSINESS PARTNER

 **KYOCERA**
Document Solutions