

PG L2745, L2750, L2755

COMPACT, VERSATILE AND ENVIRONMENTALLY FRIENDLY

The PG L2745, PG L2750 and PG L2755 are the A4 Mono printers that guarantee speed and reliability and help improve productivity and efficiency — the perfect solution for small and medium-sized work groups.

The high performance of the system combined with modern data protection solutions and practical paper management options provide versatility, savings on management costs and maximum operational flexibility, also thanks to the ability to connect for mobile printing.

With long-lasting components and low energy consumption, the environmental impact is also lower.









Compact and sleek

Control panel and display

Configured with 4 x PF3110 Paper Trays and Caster Kit

TECHNICAL SPECIFICA	TIONS PG L2745	PG L2750	PG L2755
GENERAL Type	Desktop printer		
Technology	Monochrome laser		
Operation Panel		21-character, 5-row LCD	
Print speed, A4	up to 45 ppm	up to 50 ppm	up to 55 ppm
Duplex print speed, A4	up to 22.5 ppm	up to 35.5 ppm	up to 39.5 ppm
Print resolution		1200 x 1200 dpi	1 11
Warm-up time	16 sec or less	20 sec or less	25 sec or less
First print out time	5.3 sec or less	5.4 sec or less	4.5 or less
Dimensions (W x D x H)	380 x 410 x 285 mm	380 x 410 x 320 mm	
Maximum dimensions (W x D x H)	390 x 416 x 308 mm	390 x 416 x 343 mm	
Basic unit weight	14.6 kg (including toner)	16.1 kg (including toner)	
Power supply		AC 220 V ~ 240 V, 50/60 Hz	
Random code	B2322	B2321	B2320
PAPER HANDLING Input paper capacity	Multi-use bypass for 100 sheets, 60-220 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (70 x 140 mm-216 x 356 mm), paper for banners up to 915 mm; Universal standard tray: 500 sheets, 60-120 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (140x210 mm - 216x356 mm)	Multi-use bypass for 100 sheets, 60-220 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (70 x 140 mm-216 x 356 mm), paper for banners up to 915 mm; Universal standard tray: 500 sheets, 60-120 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (105x148 mm - 216x356 mm)	
Maximum input paper capacity		2,600 A4 sheets (with additional trays)	
Duplex printing		mode, 60-120 g/m², A4, A5, B5, Letter, Legal, Custom	
Output paper capacity	250 sheets face down with paper sensor		n with paper sensor and with optional PT-320
CONTROLLER			
Processor	ARM Cortex-A53 Dual core 1.4 GHz		
Memory	Standard: 512 MB; max. 2.5 GB (optional)		
Interfaces	USB 2.0 (Hi-Speed), 2 USB Host Interfaces, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Wireless LAN optional (IEEE 802.11b/g/n), 2 slot eKUIO for optional internal print server or SSD hard disk; slot for optional SD/SDHC		
Emulations	PCL6 (5e/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and Open XPS, PPML, direct print support for TIFF/JPEG, URF, PWG Raster, PCLm, IBM Proprinter, Line Printer, Epson LQ-850		
Operating Systems Fonts/Barcodes	All current Windows operating systems, MAC OS X 10.9 or later, Chrome OS, Linux 93 scalable fonts (PCL6, KPDL3), 4 fonts (Calibri), 4 fonts (Cambria), 1 font Bitmap, 45 one-dimensional barcode types,		
Printing features	1 two-dimensional barcode type (PDF417) PDF Direct Print, Internet IPP 1.0 printing, E-mail printing, WSD printing, Secure IPP printing via TLS, local and network authentication,		
	network data encryption IPsec, HTTPS, LDAP via TLS, SNMPv3, SMTP via TLS, encrypted PDF Direct Print, printing for the Chrome operating system		
Mobile printing supports	Olivetti Mobile Print App for iOS and Android, AirPrint®, Wi-Fi Direct® (optional)		
CONSUMABLES	The average life of toner cartridges complies with the ISO/IEC 19752 standard		
Black toner cartridge (B1446)	Up to 12,500 A4 pages. Starter toner up to 6,000 A4 pages		
Black toner cartridge (B1447)		Up to 15,500 A4 pages. Starter toner up to 8,000 A4 pages	
Black toner cartridge (B1448)		Starter toner up to 8,000 A4 pages	Up to 25,000 A4 pages.
	11		Starter toner up to 10,000 A4 pages
Maintenance kit (B1449) Maintenance kit (B1451)	Up to 300,000 pages	Up to 500	000 pages
OPTIONS	DF 2446	1.47.45.DE 1.57.45.	246 256 1/4 1/4 1/4 1/4
PF-3110 tray (B3928)	PF-3110: max 500 sheets, 60-120 g/m²; A4, A5, B5, Letter, Legal, Custom (92x162 mm-216x356 mm) (max 4 optional trays)		
High capacity tray PF-3100 (B3404)	Max 2,000 sheets, 60-220 g/m²; A4, A5, B5, Letter, Custom (76x148 - 216x305 mm);		
and support base PB-325 (B4367)	not compatible with PF-3110 Paper output tray 250 sheets face-up		
PT-320 (B4365)	6.11		
CB-365W L (B3687)	Cabinet with paper compartment (low) 38 cm x 41 cm x 25 cm Cabinet with paper compartment (high) 38 cm x 41 cm x 51 cm		
CB-360W H (B3686)			
CA-3100 (B2331)	Caster Kit: unit with casters for added stability. Mandatory when installing 4 optional paper feed trays MM-20 (1GB)/MM-21 (2GB), DDR3-144pin DIMM		
Memory expansions	MM-20 (1GB)/MM-21 (2GB), DDR3-144pin DIMM 64 GB SSD hard disk		
HD-17 (B2323) HD-18 (B2324)		256 GB SSD hard disk	
HD-19 (B2325)	512 GB SSD hard disk		
IB-32B (B3405)	IEEE1284 Interface		
IB-37 (B2215)/IB-38 (B2216)	Wireless LAN (802.11b/g/n) with Wi-Fi Direct®: IB-37 2.4-GHz and 5-GHz; IB-38 2.4-GHz		
IB-53 (B2341)	Gigabit Ethernet board 10 BaseT/100 BaseTX/1000 BaseT		
IB-54 (B2342)/IB-55 (B2343) UG-33 (B8403)	Wireless network interface (802.11b/g/n): IB-54 2.4-GHz and 5-GHz; IB-55 2.4-GHz		
	ThinPrint support TPM (Trusted Platform Module)		
UG-50 (B2326) USB IC-Card reader	Support for various types of authentication/card/badge reading		
(+ Card Authentication kit (B) - B8237) Card Reader Holder 10 (B4845)	Plastic support to integrate the badge reader into the control panel		

